

Rotary Hammer

HR4003C

1 100 W • SDS-Max • 40 mm • 8.3 J

Great dual-action combi hammer

An Efficient 1 100 W combi hammer for SDS-MAX blades. Masonry drilling capacity of 40 mm and impact energy of 8.3 J. With its drilling and chipping functions, this tool is an ideal choice for renovation and building work.



Technical specifications

Continuous Input Power	1100 W
No load speed	250 - 500 min ⁻¹
Impacts per Minute (IPM)	1450 - 2900 min ⁻¹
Max. Drilling Diameter in Concrete	40 mm
Optimum Drilling Diameter Range in Concrete	16 - 30 mm
Impact Energy	8,3 J
Drilling diameter with TCT core bit	105 mm
Power Supply Cord	5,0 m
Plastic Carrying Case	✓
Sound Power Level (L _{WA})	103 dB(A)
Sound Pressure Level (L _{pA})	92 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level (3 axes), Impact Drilling	10,0 m/s ²
Vibration: Chiselling	7,6 m/s ²

EAN 0088381651370

Link to product - www.makitauk.com



Related products

Standard AC

123138-5

Straight Side Handle



123259-3

Side Handle 73 Assembly

198995-0

Grease Vessel Set

331955-1

Depth Gauge

443122-7

Cleaning Cloth



687010-0

Band, 5704R

Optional AC

199144-2

Dust Extraction Attachment



Other

User manual

Parts drawing