

Rotary Hammer LXT®

DHR242

18V • SDS-PLUS • 24 mm • 2.0 J

Professional brushless, three-mode rotary hammer

An efficient rotary hammer for SDS-PLUS bits with an anti-vibration handle. Suitable for impact and unstressed drilling, plus chipping. Speed range of 0 – 950 min⁻¹. Impact energy of 2.0 J and max. drilling capacity of 24 mm in concrete.



Technical specifications

Nominal Battery Voltage	18 V
Voltage LXT	✓
Brushless Motor	✓
Impact Energy	2,0 J
Optimum Drilling Diameter Range in Concrete	6 - 12 mm
Max. Drilling Diameter in Concrete	24 mm
Max. Drilling Diameter in Wood	27 mm
Max. Drilling Diameter in Steel	13 mm
Impacts per Minute (IPM)	0 - 4700 min ⁻¹
No load speed	0 - 950 min ⁻¹
Sound Power Level (L _{WA})	101 dB(A)
Sound Pressure Level (L _{pA})	90 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level (3 axes), Drilling	3,5 m/s ²

User benefits

- Brushless maintenance-free and long-life motor
- Body model - delivered without battery and charger.
- Battery protection circuit protects against overloading, over-discharging and over-heating

Link to product - www.makita.uk.com



Related products

■ Optional AC

183477-5

Grease for SDS Drills and Hammers



■ Other

User manual

Parts drawing