

# Rotary Hammer LXT ®

## DHR263

18V X2 • SDS-PLUS • 26 mm • 2.5 J

### Professional, robust three-mode rotary hammer

An efficient rotary hammer with anti-vibration rear and side handles, accepts SDS-PLUS bits. Two 18V LXT batteries achieve a high voltage of 36V. Suited to impact and unstressed drilling and chipping. Speed range of 0 – 1 200 min<sup>-1</sup>. Impact energy of 2.5 J and max. drilling capacity of 26 mm in concrete.



### Technical specifications

Nominal Battery Voltage	2 x 18 V
Voltage LXT	✓
Impact Energy	2,5 J
Optimum Drilling Diameter Range in Concrete	6 - 16 mm
Max. Drilling Diameter in Concrete	26 mm
Max. Drilling Diameter in Wood	32 mm
Max. Drilling Diameter in Steel	13 mm
Impacts per Minute (IPM)	0 - 5000 min <sup>-1</sup>
No load speed	0 - 1250 min <sup>-1</sup>
Sound Power Level (L <sub>WA</sub> )	102 dB(A)
Sound Pressure Level (L <sub>pA</sub> )	94 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level (3 axes), Drilling	3,0 m/s <sup>2</sup>
Vibration Level (3 axes), Impact Drilling	14,5 m/s <sup>2</sup>

### User benefits

- LED light illuminates the work site
- Battery protection circuit protects against overloading, over-discharging and over-heating

Link to product - [www.makitauk.com](http://www.makitauk.com)



# Related products

## ■ **Optional AC**

183477-5

Grease for SDS Drills and Hammers



---

## ■ **Other**

User manual

Parts drawing