

Reciprocating Saw LXT®

DJR187

18V • 0 – 3 000 min⁻¹ • 32 mm

Efficient brushless reciprocating saw

An efficient brushless reciprocating saw for spark-free cutting of metal and demolition work for professional use. Two speed settings, stroke length of 32 mm and stroke rate of 0 – 2 800 min⁻¹ with continuous control from the switch. Quick-release blade attachment.



Technical specifications

Nominal Battery Voltage	18 V
Voltage LXT	✓
Brushless Motor	✓
Strokes per Minute (SPM)	0 - 2300 / 3000 min ⁻¹
Length of Stroke	32 mm
Max. Cutting Capacity in Wood (90°)	255 mm
Max. Cutting Capacity in Steel Pipe	130 mm
Sound Power Level (L _{WA})	95 dB(A)
Sound Pressure Level (L _{pA})	84 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level (3 axes)	16,5 m/s ²
Vibration Uncertainty (K Factor)	1,5 m/s ²
Tool weight with battery (EPTA)	3,4 - 3,8 kg
Product Dimensions (L x W x H):	439 x 83 x 231 mm
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion

User benefits

- LED light illuminates the work site
- Battery protection system automatically shuts off power when the battery level is low

Link to product - www.makita.dk



Related products

Optional AC

821620-5

Plastic Carrying Case

BL1830B

Battery LXT® 3,0 Ah

BL1850B

Battery LXT® 5,0 Ah



BL1820B

Battery LXT® 2,0 Ah



BL1840B

Battery LXT® 4,0 Ah



BL1860B

Battery LXT® 6,0 Ah



Other

User manual

Parts drawing